

## DECLARATION OF PERFORMANCE

No. ODEK "A" CPR 2017-09-27

1. Unique identification code of the product-type:

**ODEK "A"**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

**ODEK "A" 6,5 - 40mm**

***Combi plywood – birch veneers on each face and alternate veneers of alder, glued with phenol-formaldehyde resins; high water resistance.***

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**External use as structural components in exterior conditions (EN 636-3S)**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**"ODEK" Ukraine LLC  
9, Zavodska Street, Settlement Orzhiv, Rivne region,  
Ukraine, 35313, tel.:+380 362 693 608, fax:+380 362 693 610, e-mail:  
[marketing@odekdns.utel.net.ua](mailto:marketing@odekdns.utel.net.ua)**

5. Name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**ODEK Holland b.v.  
Cypresbaan 9, 2908 LT CAPELLE AAN DEN IJSSEL, The Netherlands  
tel.: +41 79 433 33 38,  
e-mail: [odek@euronet.nl](mailto:odek@euronet.nl)**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 2+**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**Notified factory production control certification body Institute SKH No. 0502 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.**

8. Declared performance

Essential characteristics	Performance	Harmonised technical specification
<b>Strength for structural use (bending)</b> - $f_{m\parallel}$ , tickness: 6,5mm 9,5mm 12mm 15mm 18mm 21mm 24mm 27mm 30mm 35mm 40mm  - $f_{m\perp}$ , tickness: 6,5mm 9,5mm 12mm 15mm 18mm 21mm 24mm 27mm 30mm 35mm 40mm	63.0 N/mm <sup>2</sup> 52.1 N/mm <sup>2</sup> 45.3 N/mm <sup>2</sup> 41.6 N/mm <sup>2</sup> 40.0 N/mm <sup>2</sup> 38.4 N/mm <sup>2</sup> 35.1 N/mm <sup>2</sup> 33.4 N/mm <sup>2</sup> 32.2 N/mm <sup>2</sup> 31.3 N/mm <sup>2</sup> 30.9 N/mm <sup>2</sup>  21.0 N/mm <sup>2</sup> 22.5 N/mm <sup>2</sup> 21.8 N/mm <sup>2</sup> 21.2 N/mm <sup>2</sup> 20.7 N/mm <sup>2</sup> 20.4 N/mm <sup>2</sup> 20.1 N/mm <sup>2</sup> 19.8 N/mm <sup>2</sup> 19.6 N/mm <sup>2</sup> 19.3 N/mm <sup>2</sup> 19.2 N/mm <sup>2</sup>	EN 13986:2015
<b>Stiffness for structural use (bending)</b> - $E_{m\parallel}$ , tickness: 6,5mm 9,5mm 12mm 15mm 18mm 21mm 24mm 27mm 30mm 35mm 40mm  - $E_{m\perp}$ , tickness: 6,5mm 9,5mm 12mm 15mm 18mm 21mm 24mm 27mm 30mm 35mm 40mm	12635 11088 10455 10306 9855 9716 9639 9578 9285 9146 9164  3558 4409 4809 5039 5188 5291 5367 5425 5471 5538 5586	
Bonding quality (moisture resistance)	EN 636-3 S	
Release of formaldehyde	E1	
Reaction to fire	class F class D-s2,d0	
Water vapour permeability $\mu$	NPD	
Airborne sound insulation	NPD	
Thermal conductivity $\lambda$	NPD	
Mechanical durability	NPD	
Biological durability	NPD	
Release (content) of pentachlorophenol (PCP)	NPD	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Anatoliy Tyshchuk – deputy general manager on quality and certification  
(name and function)

Orzhiv, 27-09-2017  
(place and date of issue)



(signature)